

Duo-Touch™



Duo-Touch™

The Smallest, Lightest Rugged Tablet PC

WIRELESS

Upgradable, Modular Design for Unparalleled Performance and Flexibility

- EV-DO
- EDGE/GPRS/UMTS/HSDPA
- 802.11 b/g WLAN
- Bluetooth
- Up to 3 RF modems and GPS at the same time
- Various combinations available depending on specific requirements

ERGONOMIC

Designed for rugged mobility

- One handed operation
- Under 2 kg (4.1lbs)
- Intuitive design for easy operation

POWERFUL

For today and for the future

- Intel Pentium m Processor 733 at 1.1 GHz
- 512 – 1280 MB DDR2 RAM 533 MHz

RUGGED

Providing for computing anywhere, anytime

- Vibration Mil-Std 810F, 514.5 and ASTM 4169-99 truck assurance level II schedule B
- Dust per IP-54
- Hazardous Location Class 1 Division 2 (UL 1604)
- 26 repeated 3 ft. drops onto plywood over concrete per MIL-STD 810F, 516, 5 IV
- Blowing rain/water resistance at 4" per hour at approximately 40 PSI for 10 minutes on all 6 axes per MIL-STD 810F, 5064II

GENERAL DYNAMICS
Itronix

Itronix brings the wireless performance and rugged capabilities of the GoBook line to the demanding world of Tablet PC's.

The Duo-Touch is a rugged "slate" Tablet PC that puts the power and flexibility of tablet computing to work in environmentally-challenging situations. Lightweight and ergonomic –enabling one-handed operation- the Duo-Touch includes both an active digitizer and passive touch screen and boasts the ruggedness and weatherization you've come to expect from Itronix. With multiple integrated wireless technologies, including EDGE / GPRS / UMTS / HSDPA, EV-DO, 802.11b/g, Class II Bluetooth and GPS, the Duo-Touch is ready for any wireless network. It offers the performance and flexibility needed to keep field-deployed, mission-critical workers productive. Itronix took the best aspects of Tablet PC technology and improved on them for high-performance mobile applications. It is Ideal for industries such as insurance, telecommunications, public safety, utility and energy, and commercial field service. The Duo-Touch is backed by Itronix' innovative "total-solutions" approach for implementation at the enterprise level. Whether your field team is new to wireless computing or if you are looking to enhance your existing mobile computing line-up, the Duo-Touch will provide years of performance at the stroke of a pen or touch of a finger.



Product specification

Compact Size:

- Length: 10.6" (27.0 cm)
- Width: 7.2" (18.4 cm)
- Depth: 1.65" (4.2 cm)

Weight:

- 4.1 lbs (less than 2.0 KG)

Processor/Memory:

- Intel® Pentium® M Processor 733 at 1.1 GHz with 2MB L2 cache
- 512 to 1280MB DDR2 RAM 533 MHz

Storage:

- Shock mounted 2.5" 40 GB and 80 GB hard disk drive (w/optional heater)
- Optional 16 GB Solid State Hard Disk Drive

Power:

- Smart 3900 mAh (40.0W) Lithium-Ion main battery pack
- 3900 mAh (40.0W) Lithium-Ion expansion battery pack option

Display:

- 8.4" SVGA TFT Transmissive display
- Optional DynaVue™ Patent- Pending technology for optimum outdoor viewability
- DynaVue™ exceeds the minimum contrast ratio as required for bright sunlight per DOD-STD-3009

Pointing Device:

- Digitizer Control Panel Touchscreen and Passive Touchscreen Standard

Operating System:

- Microsoft Windows XP Tablet PC Edition 2005

Interfaces:

- PC Card slot for (1) Type I or II card with 32 bit Card Bus 2.1 Interface
- Compact Flash slot for (1) Type I or II card
- Built-in RJ-11 and RJ-45 jacks for integrated fax/modem and Ethernet
- (2) USB 2.0 connectors
- 26-pin docking connector
- External speaker and microphone jacks
- Connector for expansion Battery

Audio:

- Internal microphone and speaker
- PCI Audio with AC-97 compliance

Integrated Wireline Communications:

- 56 Kbps V.92 fax/modem
- 10/100/1000 Mbit Base-T Ethernet LAN

Optional Integrated Wireless Communications:

- EV-DO
- EDGE/GPRS/UMTS/HSDPA
- 802.11b/g WLAN
- Bluetooth
- Up to 3 RF modems and GPS can be integrated at one time
- GPS

Hot Keys:

- Enter
- Up/Down Arrows
- Escape
- Security (Secure Attention Sequence)
- Rotate Display Image (landscape/ portrait)
- Function Key
- Suspend/Power on/off
- WLAN/Bluetooth on/off
- On/off switch for all radio's

Options:

- Desk Mount with 15-pin external video (CRT) port
- (2) USB ports, and expansion Battery Charger
- Vehicle power supply
- Vehicle dock with optional keyboard, lock, and serial, USB, and external monitor connectors

- Hand strap
- Carry cases for system and accessories with handle and optional shoulder straps
- Mobility XE™, seamless roaming connectivity

Environmental:

- Die-cast magnesium for structural components
- Operating temperature -20° to 60° C (-4° to 140° F)
- Storage temperature -55° to 75° C (-67° to 167° F)
- Optional Compliance with UL 1604 Class I, Division 2, Group A, B, C and D for Hazardous Locations
- 26 repeated 3ft drops onto plywood over concrete per MIL-STD 810F, 516.5 IV
- Blowing rain/water resistance at 4" per hour at approximately 40 psi for 10 minutes on all 6 axes per MIL-STD 810F, 506.4 II
- Dust per IP-54
- Vibration per MIL-STD 810F, 514.5 and ASTM 4169-99 truck assurance level II, Schedule E
- Boot Temperature 0° C without Hard Drive Heater; -20° C with Hard Drive Heater (with external power)
- CE Mark

GENERAL DYNAMICS

Itronix

North America Head Office: 12825 E. Mirabeau Parkway • Spokane Valley, WA 99216 • Tel: +1-800-441-1309, +1-509-624-6600 • Fax: +1-509-626-4203 • Email: sales@itronix.com • www.gd-itronix.com

EMEA Head Office: Earlplace Business Park, Fletchamstead Highway, Coventry, CV4 9UR UK • Tel: +44(0) 24 7671 4800 • Fax: +44(0) 24 7671 5677 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

Germany: Tel: +49 211 5 23 91 459 • Fax: +49 211 5 23 91 200 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

France: Parc d'Affaires Silic, 74 Rue d'Arcueil, BP 10405, 94573 RUNGIS Cedex, France • Tel: +33(0) 1 46 87 80 09 • Fax: +33(0) 1 45 60 55 95 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

Canada: 2783 Thamesgate Dr., Mississauga, Ontario, L4T 1G5, Canada • Tel: +1-800-571-5434 • +1-905-672-7007 • Fax: 1-905-672-3999 • Email: sales@itronix.com • www.gd-itronix.com

Asia: 5th Floor-2, No. 80, Chung-Hsiao East Road Sec. 2, Taipei 100, Taiwan • Tel: +866 2 2393 0660 • Fax: +866 2 2395 5256 • Email: sales@itronix.com.tw

© 2007 General Dynamics. All rights reserved. General Dynamics Itronix Corporation reserves the right to make changes in its products and specifications at anytime and without notice. All trademarks indicated as such herein are trademarks of General Dynamics Itronix. All other product and service names are the property of their respective owners. ® Reg. U.S. Pat. and Tm. Off. V.3.07/07 4T